


LED T8 Tubes CL

Magnolux LED T8 Tubes are compatible with both, magnetic and electronic ballasts, and are the most efficient and environmentally friendly alternative to traditional fluorescent tubes.



LED T8 Tube CL - EM25-1500

HIGHLIGHTS

- » high energy efficiency
- » lifetime up to 25.000 hours
- » EM and CEM-models are compatibel with magnetic and electric ballast

APPLICATION AREA

Offices, Hotels, Supermarkets, Warehouses, Commercial and Industrial Buildings, Airports, Schools, Hospitals, Parking Decks, etc.



SPECIFICATIONS

Artikel Number	101175
Product Name	LED T8 Tube CL
Model	EM25-1500
Socket	G13 - 26 mm
Lumen Output	2700 Lumen
Power Consumption	25 Watt
Input Voltage/Hertz	85-265 V / 50-60 Hz
Power Factor	>0,95
Light Color	5500 Kelvin
Color Rendering Index	>80
LED Type	SMD
Beam Angle	120°
Lifetime	25000 h
Environment Temperature	-10°C / +40°C
Material	Alu silver/PC milky
Product Dimensions	Ø 26 mm, L 1500 mm
Certificates	CE, RoHs, EN62471
PCS/Package	25
Packaging Size	1540 x 215 x 220 mm
Weight/Packaging	22000 g
Product Info	compatible with magnetic/electronic ballast, use max. 2 tubes on one ballast