

**GRAH**<sup>®</sup>  
LED LIGHTING



## LED Street Lighting LSL - LSL60 II74-4000

### HIGHLIGHTS

- » asymmetric distribution of luminosity for optimal lighting
- » optimized heat dissipation extends life time
- » multi layer protection of casing for excellent durability
- » dimming (1-10V) optional

### APPLICATION AREA

Urban Traffic Roads, Collector Roads, Junctions, Parking Lots, more demanding Industrial Buildings



## SPECIFICATIONS

|                         |   |
|-------------------------|---|
| <b>Artikel Number</b>   | <b>100028</b>                                       |
| <b>Product Name</b>     | <b>LED Street Lighting LSL</b>                      |
| <b>Model</b>            | <b>LSL60 II74-4000</b>                              |
| Lumen Output            | 8700 Lumen  |
| Power Consumption       | 74 Watt   |
| Input Voltage/Hertz     | 110-250 V / 50-60 Hz                                |
| Light Color             | 4000 Kelvin   |
| Dimming                 | dimmable 1-100%                                     |
| Lifetime                | 60000 h   |
| Environment Temperature | -30°C / +60°C                                       |
| Operating Temperature   | +55°C   |
| Material                | Alu-Die-Casting<br>RAL9006/PMMA                     |
| Product Dimensions      | 720 x 465 x 139 mm                                  |
| Product Weight          | 7000 g  |
| Certificates            | CE, RoHS  |
| Safety Class            | II  |
| Safety Type             | IP66  |
| Shock Resistance        | IK08  |
| Product Info            | AA optics asymmetric,<br>excl. pole connection part |