

LED Downlights ST

Magnolux LED Downlights of ST Series with excellent luminance are the most efficient and environmentally friendly alternative to traditional downlights.



LED Downlight ST - R70 7-620L

HIGHLIGHTS

- » lighting direction adjustable (R70 and R140 models)
- » lifetime up to 50.000 hours
- » various designs with simple white or elegant silver
- » lens or reflector optional

APPLICATION AREA

Private Households, Offices, Commercial and Public Buildings, Industry, Hotels, etc.

SPECIFICATIONS

Artikel Number	100257
Product Name	LED Downlight ST
Model	R70 7-620L
Lumen Output	620 Lumen
LED Power	7 Watt
Power Consumption	8.5 Watt
Input Voltage/Hertz	220-240 V / 50-60 Hz
Power Factor	>0,8
Light Color	4000 Kelvin
Color Rendering Index	>83
LED Type	COB
Beam Angle	38°
Dimming	Dimming with TRIAC Driver
Lifetime	50000 h
Environment Temperature	-25°C / +65°C
Operating Temperature	-25°C / +65°C
Material	Alu white/PMMA Lens
Product Dimensions	Ø 83 mm x H 58 mm
Certificates	CE, RoHS
Safety Class	III SELV
Safety Type	IP43
PCS/Package	1
Packaging Size	110 x 110 x 105 mm
Product Info	Ceiling cut-out: 70 mm

