

### LED Downlights ST

Magnolux LED Downlights of ST Series with excellent luminance are the most efficient and environmentally friendly alternative to traditional downlights.



## LED Downlight ST - R97 7-580

### HIGHLIGHTS

- » lighting direction adjustable (R70 and R140 models)
- » lifetime up to 50.000 hours
- » various designs with simple white or elegant silver
- » lens or reflector optional

### APPLICATION AREA

Private Households, Offices, Commercial and Public Buildings, Industry, Hotels, etc.



# SPECIFICATIONS

<b>Artikel Number</b>	<b>101264</b>
<b>Product Name</b>	<b>LED Downlight ST</b>
<b>Model</b>	<b>R97 7-580</b>
Lumen Output	580 Lumen
LED Power	7 Watt
Power Consumption	8.5 Watt
Input Voltage/Hertz	220-240 V / 50-60 Hz
Power Factor	>0,8
Light Color	3000 Kelvin
Color Rendering Index	>83
LED Type	COB
Beam Angle	60°
Lifetime	50000 h
Environment Temperature	-25°C / +65°C
Operating Temperature	-25°C / +65°C
Material	Aluminium white/Aluminium Reflector
Product Dimensions	Ø 105 mm x H 100 mm
Certificates	CE, RoHS
Safety Class	III SELV
Safety Type	IP43
PCS/Package	1
Packaging Size	150 x 150 x 140 mm
Product Info	Ceiling cut-out: 97 mm