

LED Downlights ST

Magnolux LED Downlights of ST Series with excellent luminance are the most efficient and environmentally friendly alternative to traditional downlights.





LED Downlight ST - R70 7-620

HIGHLIGHTS

- » lighting direction adjustable (R70 and R140 models)
- » lifetime up to 50.000 hours
- » various designs with simple white or elegant silver
- » lens or reflector optional

APPLICATION AREA

Private Households, Offices, Commercial and Public Buildings, Industry, Hotels, etc.











SPECIFICATIONS

100256
LED Downlight ST
R70 7-620

Lumen Output 620 Lumen
LED Power 7 Watt
Power Consumption 8.5 Watt

Input Voltage/Hertz 220-240 V / 50-60 Hz Power Factor >0,8

Power Factor >0,8

Light Color 4000 Kelvin

Color Rendering Index >83

LED Type COB Beam Angle 38°

Dimming With TRIAC

Driver

Lifetime 50000 h

Environment Temperature -25°C / +65°C

Operating Termperature -25°C / +65°C

Material Alu white/Aluminium Reflector

Product Dimensions Ø 83 mm x H 58 mm

Certificates CE, RoHs

Safety Class III SELV

Safety Type IP43 PCS/Package 1

Packaging Size 105 x 105 x 75 mm
Product Info Ceiling cut-out: 70 mm