

### LED Downlights ST

Magnolux LED Downlights of ST Series with excellent luminance are the most efficient and environmentally friendly alternative to traditional downlights.



## LED Downlight ST - R140 30-2080L

### HIGHLIGHTS

- » lighting direction adjustable (R70 and R140 models)
- » lifetime up to 50.000 hours
- » various designs with simple white or elegant silver
- » lens or reflector optional

### APPLICATION AREA

Private Households, Offices, Commercial and Public Buildings, Industry, Hotels, etc.



## SPECIFICATIONS

|                         |                         |
|-------------------------|-------------------------|
| <b>Artikel Number</b>   | <b>101106</b>           |
| <b>Product Name</b>     | <b>LED Downlight ST</b> |
| <b>Model</b>            | <b>R140 30-2080L</b>    |
| Lumen Output            | 2080 Lumen              |
| Power Consumption       | 30 Watt                 |
| Input Voltage/Hertz     | 110-240 V / 50-60 Hz    |
| Power Factor            | >0,8                    |
| Light Color             | 3000 Kelvin             |
| Color Rendering Index   | >83                     |
| LED Type                | COB                     |
| Beam Angle              | 38°                     |
| Lifetime                | 25000 h                 |
| Environment Temperature | -25°C / +65°C           |
| Operating Temperature   | -25°C / +65°C           |
| Material                | Aluminium white/PMMA    |
| Product Dimensions      | Ø 150 mm, H 80 mm       |
| Certificates            | CE, RoHs                |
| Safety Class            | III SELV                |
| Safety Type             | IP43                    |
| PCS/Package             | 1                       |
| Packaging Size          | 160 x 160 x 80 mm       |
| Product Info            | Ceiling cut-out: 140 mm |