

LED Downlights ST

Magnolux LED Downlights of ST Series with excellent luminance are the most efficient and environmentally friendly alternative to traditional downlights.



LED Downlight ST - R70 7-580

HIGHLIGHTS

- » lighting direction adjustable (R70 and R140 models)
- » lifetime up to 50.000 hours
- » various designs with simple white or elegant silver
- » lens or reflector optional

APPLICATION AREA

Private Households, Offices, Commercial and Public Buildings, Industry, Hotels, etc.



SPECIFICATIONS

| | |
|-------------------------|--------------------------------|
| Artikel Number | 101447 |
| Product Name | LED Downlight ST |
| Model | R70 7-580 |
| Lumen Output | 580 Lumen |
| LED Power | 7 Watt |
| Power Consumption | 8.5 Watt |
| Input Voltage/Hertz | 220-240 V / 50-60 Hz |
| Power Factor | >0,8 |
| Light Color | 3000 Kelvin |
| Color Rendering Index | >83 |
| LED Type | COB |
| Beam Angle | 38° |
| Dimming | Dimming with TRIAC Driver |
| Lifetime | 50000 h |
| Environment Temperature | -25°C / +65°C |
| Operating Temperature | -25°C / +65°C |
| Material | Alu silver/Aluminium Reflector |
| Product Dimensions | Ø 83 mm x H 58 mm |
| Certificates | CE, RoHS |
| Safety Class | III SELV |
| Safety Type | IP43 |
| PCS/Package | 1 |
| Packaging Size | 105 x 105 x 75 mm |
| Product Info | Ceiling cut-out: 70 mm |