

GRAH[®]

LED LIGHTING



LED Street Lighting LSL - LSL20 I34-4000

HIGHLIGHTS

- » asymmetric distribution of luminosity for optimal lighting
- » optimized heat dissipation extends life time
- » multi layer protection of casing for excellent durability
- » dimming (1-10V) optional

APPLICATION AREA

Urban Traffic Roads, Collector Roads, Junctions, Parking Lots, more demanding Industrial Buildings

SPECIFICATIONS



| | |
|-------------------------|---|
| Artikel Number | 101521 |
| Product Name | LED Street Lighting LSL |
| Model | LSL20 I34-4000 |
| Lumen Output | 3200 Lumen |
| Power Consumption | 34 Watt |
| Input Voltage/Hertz | 110-250 V / 50-60 Hz |
| Light Color | 4000 Kelvin |
| Lifetime | 60000 h |
| Environment Temperature | -30°C / +60°C |
| Operating Temperature | +55°C |
| Material | Alu-Die-Casting RAL9006/PMMA |
| Product Dimensions | 430 x 310 x 135 mm |
| Product Weight | 3000 g |
| Certificates | CE, RoHS |
| Safety Class | I |
| Safety Type | IP66 |
| Shock Resistance | IK08 |
| Product Info | AA optics asymmetric, excl. pole connection part |