Artikel Number: 100135

MAGNOLUX

GRAH®
LED LIGHTING

LED Street Lighting LSL - LSL15 I18-4000

HIGHLIGHTS

- » asymmetrc distribution of luminosity for optimal lighting
- » optimized heat dissipation extends life time
- » multi layer protection of casing for excellent durability
- » dimming (1-10V) optional

APPLICATION AREA

Urban Traffic Roads, Collector Roads, Junctions, Parking Lots, more demanding Industrial Buildings

~ 85% ENERGY SAVING | 100% in 1 sec. | 60000h | CE | RoHs

SPECIFICATIONS

Artikel Number	**100135**
Product Name	**LED Street Lighting LSL**
Model	**LSL15 I18-4000**
Lumen Output	2000 Lumen
Power Consumption	18 Watt
Input Voltage/Hertz	110-250 V / 50-60 Hz
Light Color	4000 Kelvin
Dimming	light reduction 50%
Lifetime	60000 h
Environment Temperature	-30°C / +60°C
Operating Termperature	+55°C
Material	Alu-Die-Casting RAL9006/PMMA
Product Dimensions	430 x 200 x 130 mm
Product Weight	2000 g
Certificates	CE, RoHs
Safety Class	I
Safety Type	IP66
Shock Resistance	IK08
Product Info	AA optics asymmetric, excl. pole connection part

MAGNOLUX GmbH, Industriestrasse 3, A-4731 Prambachkirchen
Tel.: +43 7272 77146, Fax: +43 7272 77146-46, office@magnolux.com, www.magnolux.com